

- **Manual Dimmer**
0-10V Control Port
Input 220-240V AC
- **Built-in driver**
Durable and reliable power source, all in one design.
- **PC Cover**
Protect the fixture chips from the influence of growing environment




Specifications

Input Voltage: 220-240 Volt AC
Rated Power: 720W±5%
Current Consumption: 3.0A-3.3A at 720w
Power factor: 0,98
LED: LEDESTAR
PPF Efficacy: 2.7 umol/J
BTU: 2448
IP Rating: IP44
Product dimensions (LxWxH): 1100*1070*38mm
Package dimensions (LxWxH): 1140*95*565mm
Gross Weight: 8.5kg
Operating Temperature: -25-40°C
Control: Manual Dimming System, Compatible with Ralight Controller
External Dim: Yes with Ralight Controller
External Dim Connector Rj14 Connector Build in 2x
Housing Material: Aluminum
Lifetime: 50,000H
Warranty: 2 Years



Spectrum



PAR Distribution

Height of 30cm

| | | | | | |
|-----|------|------|------|------|-----|
| 207 | 350 | 378 | 380 | 360 | 210 |
| 472 | 844 | 890 | 894 | 880 | 509 |
| 575 | 1033 | 1083 | 1102 | 1072 | 610 |
| 578 | 1007 | 1059 | 1072 | 1037 | 582 |
| 474 | 813 | 837 | 853 | 830 | 470 |
| 208 | 347 | 373 | 381 | 356 | 207 |

120CM

Height of 60cm

| | | | | | |
|-----|-----|-----|-----|-----|-----|
| 234 | 322 | 367 | 368 | 322 | 230 |
| 353 | 505 | 573 | 574 | 510 | 361 |
| 420 | 609 | 695 | 700 | 617 | 429 |
| 423 | 597 | 689 | 693 | 607 | 423 |
| 355 | 495 | 559 | 565 | 496 | 347 |
| 231 | 317 | 363 | 369 | 321 | 230 |

120CM

Height of 90cm

| | | | | | |
|-----|-----|-----|-----|-----|-----|
| 206 | 259 | 288 | 290 | 259 | 204 |
| 266 | 345 | 385 | 386 | 346 | 271 |
| 303 | 397 | 446 | 447 | 399 | 309 |
| 305 | 393 | 445 | 446 | 397 | 307 |
| 269 | 344 | 382 | 383 | 341 | 268 |
| 205 | 257 | 288 | 290 | 258 | 204 |

120CM